



## DT-25N

Order No.: 10.4010

**Price upon request**

### PRODUCTINFOS

**Neodymium hi-fi tweeter, 40 W, 8  $\Omega$**

- Outstanding sound characteristics
- Silk soft dome cone with optimised geometry
- Front plate with a specially adapted design
- Very linear reproduction even of lower frequencies
- High efficiency
- Low magnetic dispersion and mechanically very compact due to the application of a high-performance neodymium magnet
- Ideally suited for building smaller speaker systems
- For high-quality standing hi-fi speakersy, e.g. in D'Appolito arrangements
- Very fine and natural sound

### TECHNICAL SPECIFICATIONS

**DT-25N**

Impedance (Z)

8  $\Omega$

**DT-25N**

Frequency range	fx-20,000 Hz
Resonant frequency (fs)	1,600 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,500 Hz
Power rating	40 W
Peak music power output	80 W
Sensitivity	95 dB/W/m
Voice coil diameter	Ø 25 mm
Magnet diameter	Ø 46 mm
Mounting cutout	Ø 50 mm
Mounting depth	17.7 mm
Dimensions	Ø 66 x 21 mm
Outside diameter	Ø 66 mm
Width	Ø 66 mm
Depth	21 mm
Admiss. ambient temp.	0-40 °C
Weight	65 g
Packing unit	1